

Ref.: 53728

snb

[illegible]

Apparatus (11) for optimizing actual woven fabrics on the basis of measured yarn data, having at least one measuring device (12) for measuring the yarn diameter, having a structure input device (13) for inputting and changing freely definable structures, having a device (14) for controlling the measuring device (12) and for evaluation and a display device (16), the actual fabric being computed and represented on the basis of the measured yarn diameters and the freely definable structure and the fact that the defined structure of the fabric can be changed making it possible to adapt and optimize the actual fabric to the measured individual yarn diameters. (In this respect see Figure 1.)

1/PRTS

09/423179
420 Recd PCT/PTO 02 NOV 1999

Date: 22 April 1998

Ref.: 53 728

Applicant: Dieter Zweigle, Ferdinand-Lassalle-Str. 54,
5 72770 Reutlingen

**APPARATUS FOR OPTIMIZING YARNS ON THE BASIS OF MEASURED
YARN DATA AND METHOD OF OPTIMIZATION**

10 The present invention relates to an apparatus for
optimizing yarns and woven fabrics on the basis of
measured yarn data and to the associated method of
optimization.

15 The development of new woven fabrics is usually carried
out with CAD systems. These known CAD systems allow
new fabrics to be developed by changing a large number
of parameters. However, in CAD systems the computation
is always based on "ideal" yarns, i.e. yarns of which
20 the diameter, fineness and tear strength is constant
over the entire yarn.

In the case of actual yarns, however, the yarn
diameters and other yarn properties are not constant
25 over the length of the yarn, as they are in the case of
"ideal yarn". For instance, actual yarns have nips,
slubs, neps etc., which of course have an effect on the
appearance of the later "actual fabric", but are not
taken into account in the development of the fabric on
30 the CAD system. This has the effect that the actual
fabric obtained often does not meet the expectations of
the designer.

The object of the invention is to improve the systems
35 for developing new fabrics and/or to optimize machine
settings or processes in yarn manufacture.

This object is achieved by providing an apparatus which makes it possible to take into account during the design of the fabric the actual values of the respective yarn and which at the same time makes it possible to adapt and/or change the structure or any desired crossover point, taking into account the visual appearance of each yarn.

With the apparatus according to the invention, it is possible by changes to each and every crossover visually to emphasize or suppress nips, slubs or neps. In some fabrics, it is precisely the visual effects achieved by irregular yarns that are desired and, by being able to define the structure freely, it is possible in the case of desired irregularities to bring them out visually by the type of respective structure.

In the apparatus according to the invention, the yarn diameter of the respective individual yarn is measured optoelectronically. On the basis of the defined type of desired structure, a three-dimensional representation of the actual yarn is computed, taking into account the individual measured values of the yarns, and is visually displayed. Each and every crossover can be changed - preferably using a schematized representation of the fabric on a screen and input with the keyboard or a mouse. The actual fabric can in turn be visually displayed and changed as much as required until the desired design is obtained.

The three-dimensional representation of the actual fabric also means that considerable amounts of yarn, machines, power and working time are saved, since it is no longer necessary to switch on the loom to see how the actual fabric looks, perhaps then to declare it a reject.

The combination of the structure input device and free selectability of the weaving density also contributes to reducing the number of rejects.

- 5 Furthermore, in a particular embodiment it is possible in the apparatus according to the invention also to measure the colours along a yarn and to transfer them into the evaluation device, so that in addition to the actual yarn diameters the actual colours can also be
10 taken into account in the computation of the actual fabric.

The invention is now explained in more detail with reference to an exemplary embodiment:

- 15 Figure 1 shows the construction of the apparatus according to the invention for optimizing actual fabrics on the basis of measured yarn data.

- 20 The apparatus 11 comprises a measuring device 12, which serves for measuring the yarn diameter, a structure input device 13, in which the respective desired structure can be freely defined and also changed, a control and evaluation device 14 and a display device
25 16, in particular a screen.

- The measuring of the yarn diameter in the measuring device 12 takes place in the measuring head, which operates on the optical principle of absolute
30 measurement. The advantage of absolute optoelectronic measurement is that the measurement is insensitive to light source aging, extraneous light, soiling, temperature and humidity and is not dependent on the colour, conductivity and lustre of the yarn to be
35 measured. Such measurement also does not require constant recalibration and input of parameters.

For the measuring of natural yarns, it is generally adequate to use a measuring head with the accuracy of

054439-1039

0.1 mm. However, depending on the type of yarn to be measured, for example in the case of yarns of man-made fibres or else in individual cases of yarns of natural fibres, measuring heads

5 with the accuracy of at least 0.01 mm
are used with preference.

In addition to the measuring head, the measuring device 12 comprises a yarn feed and electronics.

10

Such measuring heads are known from the prior art and are sold, for example, by BARCO/Belgium.

For the optimizing apparatus according to the invention
15 it is necessary that the accuracy of the yarn diameter measurement is at least 1/100 mm. The measuring of the diameter of the yarn should take place at least every 2 mm.

20 The measured values determined in the measuring device 12 are then transferred into the evaluation device 14 via a parallel interface 19. The evaluation device 14 at the same time controls the measuring device 12 by a serial interface 21.

25

Also connected to the device 14 is the device 13 for inputting and changing freely definable structures. In the structure input device 13, any possible type of crossover of the groups of threads can be defined.

30 Preferably, these are flat fabric structures. By accessing already defined structures, this device makes it possible to define individually any desired structure and to change already existing structures at any number of crossovers. The input and changing of
35 the respective structure most easily takes place using a PC, by marking the respective crossover points displayed on a screen, for example with a mouse or using the keyboard.

THE UNIVERSITY OF CHICAGO

- On the basis of this three-dimensional representation of the actual fabric, individual structures can then be changed in order to produce an individual fabric in which specific nips, slubs and/or neps due to the individual type of crossover of the threads in the fabric structure are emphasized more or suppressed. For documentation purposes, the three-dimensional

representation of the optimized actual fabric can then be *output on a printer or copier 17, preferably in colour.

- 5 If desired, the measured values can also be statistically evaluated. The statistical evaluation makes it possible to make statements about the quality of the yarns.
- 10 The statistical functions should comprise not only a statistical evaluation of an individual measured yarn which is possible at any time but also statistical evaluation taken over entire totals of series of measurements of individual yarns and/or freely
- 15 definable and selectable individual measurements of yarns and should make it possible to obtain mean values, standard deviations, variances and other statistical evaluations of the measured individual yarns and/or groups of yarns. A two-dimensional and/or
- 20 three-dimensional graphic representation of the respectively desired statistical functions is also envisaged.
- 25 In a preferred embodiment of the apparatus according to the invention, the computation and/or visual display of the fabric partially and/or completely with ideal yarns is also envisaged.
- 30 The graphic representation of the three-dimensional actual fabric may also take place in certain selectable colours, it being possible for each yarn to be assigned a colour.
- 35 The colour selection preferably takes place for each desired actual and/or ideal yarn by input of the respectively desired red-green-blue values, so that freely definable and selectable colours are available.

Of course, it is possible to store measured parameters, measured yarn diameters, statistical evaluations, computed actual fabrics, freely defined structures, parameters of the loom etc. in a data bank and call them up again as and when needed.

It is of course possible in the case of the apparatus according to the invention to import and export outside files.

10

The apparatus according to the invention also makes it possible - for example for the identification of periodic errors, such as the moirée effect - to display on the screen and also print out the measured yarn in the form of the standard yarn chart in the standardized dimensions.

20

If the resolution of the screen 16 and/or of the output device 17 is not adequate, a segmentation of the standard yarn chart into, for example, three segments is envisaged, which even in the case of a resolution limited by the hardware allows the standard yarn chart to be represented in segments at the required high resolution for identification of the periodic errors.

25

It is optionally likewise possible on the basis of the measured yarn data to have an actual weft-knitted fabric simulated, for example single-jersey, plain, plain rib, interlock, piqué etc. or else a warp-knitted fabric.

30

Of course, the knitted fabrics can also be input and changed in the structure input device (13).

D 53 728 1 10 20 25 30